


ATTENUATOR TEMPERATURE VARIABLE

DATASHEET PART SERIES: TVAXX00XXXW3S

Sheet 1 of 3
Doc# TVAXX00XXXW3S-1008145ECO-084245
Revision AF

ORDERING INFORMATION

Part Identifier: TVAXX00XXXW3S



SPECIFICATIONS

1.0 ELECTRICAL

Nominal Impedance:	50 Ω .
Frequency Range:	DC-6 GHz.
Attenuation Values Available:	1-10 dB in 1 dB increments.
Attenuation Accuracy:	@ 25°C: ± 0.5 dB @ 1 GHz.
VSWR:	1.30:1 Max @ 1 GHz.
Input Power	Negative Shifting: 2 watts cw. Positive Shifting: 0.25 watts cw. Full Rated Power to 125°C, Derated Linearly to 0 watts @ 150°C.
Temperature Coefficient of Attenuation:	-0.001, -0.002, -0.003, -0.004, -0.005, -0.006, -0.007, and -0.009 dB/dB/°C. 0.003, 0.005, 0.006, 0.007, 0.008, 0.009 dB/dB/°C.
Temperature Coefficient Tolerance:	± 0.001 dB/dB/°C.

2.0 ENVIRONMENTAL

Operating Temperature:	-55°C to +150°C.
------------------------	------------------

3.0 MARKING

Unit Marking:	dB value (X), direction of shift (N or P) and TCA shift (X).
---------------	--

4.0 QUALITY ASSURANCE

Sample Inspect Per ANSI/ASQC Z1.4 General Inspection, Level II, AQL=1.0.

Visual and Mechanical Examination for Conformance to Outline Drawing Requirements.

Sample Inspection (Destructive Testing).

Select three (3) units from lot and measure DCA every 20°C over the temperature range of

-55°C to +125°C; Calculate using linear regression, the slope of the curve.

Calculate TCA using the following formula:

$$TCA = \frac{\text{Slope}}{\text{Attenuation @ 25°C}}$$

Inspection in accordance with 824W107.

Test Data Requirements:

No Data Required for Customer.

Data Retention – 24 Months.

5.0 PACKAGING

Standard:	Tape & Reel.
-----------	--------------

ATTENUATOR TEMPERATURE VARIABLE


DATASHEET

PART SERIES: TVAXX00XXXW3S

Sheet 2 of 3
Doc# TVAXX00XXXW3S-1008145ECO-084245
Revision AF

6.0 MECHANICAL

Substrate Material:	Alumina, 96% MIL-I-10.
Terminal Material:	Thick Film, Nickel Barrier, Solder Coated.
Workmanship	Per MIL-PRF-55342.
Resistive Element:	Thick Film.
Metric Dimensions:	Provided for reference only.



Unless Otherwise Specified: TOLERANCE: X.XXX ± 0.005.

DIMENSIONS APPLY BEFORE SOLDER. ALLOW 0.015 MAX FOR ALL PRETINNED SURFACES.

ATTENUATOR TEMPERATURE VARIABLE

7.0 FOOTPRINT

Part Number	Inches						mm					
	A	B	C	D	S	W	A	B	C	D	S	W
TVAXX00XXXW3S	0.043	0.063	0.067	0.035	0.032	0.152	1.09	1.60	1.70	0.89	0.81	3.86

