


## ORDERING INFORMATION

## PART IDENTIFIER:

33-1041-XX.XX

Attenuation Value



## SPECIFICATIONS

## 1. ELECTRICAL:

Nominal Impedance:	50 ohms
Frequency Range:	925– 960 MHz
Attenuation Values Available:	1 through 20 dB in 1 dB increments
Attenuation Accuracy:	1 through 10 dB $\pm$ 0.5 dB 11 through 20 dB $\pm$ 1.0 dB
Input Power CW:	10 watts @ 100°C heat sink, derated linearly to zero power at 150°C
Peak Power:	100 watts (based on 10us pulse width and 1% duty cycle)
VSWR:	1.25:1 Max

## 2. ENVIRONMENTAL:

Operating Temperature:	-55°C to +150°C
Non-operating Temperature:	-65°C to +150°C
Temperature Coefficient:	+/-200 PPM / °C max

## 3. MARKING:

Unit Marking:	Attenuation value; legibility, and permanency per MIL-STD-130
---------------	---

## 4. QUALITY ASSURANCE:

Sample Inspect Per MIL-STD-105, Level II, 1.0% AQL.

Visual and Mechanical Examination for Conformance to Outline Drawing Requirements.  
Measure Attenuation and VSWR.  
Data Retention – Standard

## 5. PACKAGING:

Standard Packaging:	Tray
---------------------	------

## 6. MECHANICAL:



Substrate Material:	Beryllium Oxide
Resistive Film:	Thin Film
Cover Material:	Alumina
Tab Material:	Beryllium Copper

## ATTENUATOR FLANGE MOUNT 10 WATT

DATASHEET PART SERIES: 33-1041-XX.XX

Sheet 2 of 2  
Doc# 33-1041ECO-083524  
Revision A

Tab Finish: Tin/Lead  
 Flange Material: Copper  
 Flange Finish: Tin/Lead  
 Metric Dimensions: Provided for reference only.



Unless Otherwise Specified: TOLERANCE: X.XX = ± 0.02 X.XXX = ± 0.010