

ORDERING INFORMATION

PART IDENTIFIER: HR03XXXS

→ (X)=Test Code: A=Group A; B=Group B; C=Group C
→ (XX)=dB VALUE (01 – 20 dB see Table 1)

Engineering Notes:

Single lot and date code available upon request.

Test Times: Group A=2 Weeks

Group B=8 Weeks

Group C=8 Weeks

Standard Lead Time 10 weeks to build product before testing if no stock available.

Assembly DWG: N/A

TABLE 1			
ATTENUATION ACCURACY			
dB	DC - 4 GHz	4 - 8 GHz	8 - 12.4 GHz
1 - 3	±0.3	±0.5	±0.5
4 - 6	±0.4	±0.5	±0.5
7 - 10	±0.5	±0.5	±0.75
11 - 15	±0.75	+0.5, -3.0	+0.5, -3.5
16 - 20	±1.0	+0.5, -4.0	+1.0, -6.0

SPECIFICATIONS

1. ELECTRICAL:

Nominal Impedance: 50 Ω
 Frequency Range: DC – 12.4 GHz
 Attenuation Values Available: 1-20 dB in 1 dB Increments
 Attenuation Accuracy: See Table 1
 Attenuation Stability: 0.0001 dB/dB/°C
 VSWR: DC - 4 GHz – 1.25, 4 – 8 GHz – 1.35, 8 – 12.4 GHz – 1.50
 Input Power: 2 Watts CW
 Full Rated Power To 125°C, Derated Linearly to 0 Watts at 150°C.
 Peak Power, 50 Watts for 10 μ S Pulse Width @ 1% Duty Cycle.

2. ENVIRONMENTAL:

Altitude: Non-Operating: Sea Level to 50,000 Feet.
 Operating: Sea Level to 50,000 Feet.
 Temperature Range: Non-Operating: -55°C to +150°C
 Operating: -55°C to +150°C
 Vibration: Per MIL-STD-202, Method 204, Cond. D.
 Shock: Per MIL-STD-202, Method 213, Cond. I.
 Moisture Resistance: Per MIL-STD-202, Method 106 except sub-cycle steps 7A, and 7B and
 Polarization and Load are not applicable.

3. MARKING:

Unit Marking: "dB Value" Legibility and Permanency per MIL-STD-130.

4. QUALITY ASSURANCE:

Verify 100% visual pre-cap inspection performed per TP-8965.

Perform Group A, B, and/or C testing as indicated by the part number per TP-8965.

Test Data Requirements:

Test Data required for customer: See paragraph 5.0 of TP-8965.

Data retention: 24 Months.

Test samples required for customer: See paragraph 5.0 of TP-8965.

5. PACKAGING:


Standard Pack per 755W002 (Serialized Waffle Pack).

6. MECHANICAL:

Substrate Material:	Alumina 96%, MIL - I – 10.
Resistive Element Material:	Thin Film, Tantalum Nitride.
Terminal Material:	Thick Film, Nickel Barrier, Solder Fuse Coated.
Metric Dimensions [mm]:	Provided for reference information only.
Workmanship:	Per MIL-PRF-55342.
Outline Drawing:	See Sheet 3.


ATTENUATOR HIGH RELIABILITY CHIP

DATASHEET PART SERIES: HR03XXXS

Sheet 3 of 3
Doc# HR03XXXS-1009885ECO-082606
Revision B

* DIMENSIONS APPLY BEFORE SOLDER, ALLOW
0.015 MAX FOR ALL PRETINNED SURFACES.

POWER RATING AND DERATING



Unless Otherwise Specified Dimensions are in Inches: Tolerance X.XXX = ±0.005