

ATTENUATOR


DATASHEET PART SERIES: TS06XXS

Sheet 1 of 3
Doc# 1016065ECO-082519
Revision D

ORDERING INFORMATION

Part Identifier:

TS06XXS

Attenuation
Value (dB)

SPECIFICATIONS

1.0 ELECTRICAL

Nominal Impedance:	50 Ω
Frequency Range:	DC - 20 GHz
Attenuation Values Available:	0 – 12; 15,20 dB (See Table)
Attenuation Accuracy:	See Table
Input Power CW:	0.5-3W based on value (0-1dB 3W; 2-3dB 1W; 4-12,15,20dB 0.5W)
Peak Power:	10X CW (1 μ s pulse width, 1% duty cycle)
VSWR:	See Table

Attenuation Value (dB)	Attenuation Accuracy (dB)		VSWR (x:1 Typical*)	
	DC – 10 GHz	10 – 20 GHz	DC – 10 GHz	10 – 20 GHz
0	CONTINUITY ONLY			
1 - 9	± 0.50	± 0.50	1.25:1	1.35:1
10-12,15,20	± 0.75	± 1.00	1.25:1	1.35:1

*For Actual Measurements See Website

2.0 ENVIRONMENTAL

Operating Temperature:	-55°C to +150°C
Non-operating Temperature:	-65°C to +150°C
Temperature Coefficient:	+/-200 PPM / °C max

3.0 MARKING

Unit Marking:	dB Value and Alignment Dot
---------------	----------------------------

4.0 QUALITY ASSURANCE

Sample Inspect Per MIL-STD-105, Level II, 1.0% AQL.

Visual and Mechanical Inspection for Conformance to Outline Drawing

Measure Attenuation and VSWR

Data Retention - Standard

5.0 PACKAGING

Standard Packaging:	Tape and Reel
---------------------	---------------



ATTENUATOR

DATASHEET PART SERIES: TS06XXS

Sheet 2 of 3
Doc# 1016065ECO-082519
Revision D

6.0 MECHANICAL

Substrate Material:	Alumina
Resistive Film	Tantalum Nitride
Terminal Material	Thin Film Palladium
Final Finish	60/40 SnPb Solder over Nickel Plating
Protective Coating	Silicon Nitride (Due to the properties of this material slight variations in color are normal)
Metric Dimensions	Provided for Reference Only




Unless Otherwise Specified: TOLERANCE: X.XX = ± 0.01 X.XXX = ± 0.005

ATTENUATOR


DATASHEET PART SERIES: TS06XXS

Sheet 3 of 3
Doc# 1016065ECO-082519
Revision D

7.0 TYPICAL PERFORMANCE AT 25°C



8.0 RECOMMENDED PCB LAYOUT

SUGGESTED MOUNTING

inches						mm					
A	B	C	D	S	W	A	B	C	D	S	W
0.012	0.012	0.040	0.008	0.021	0.068	0.30	0.30	1.02	0.20	0.53	1.73