

ORDERING INFORMATION

PART IDENTIFIER: CT2010S

SPECIFICATIONS

1. ELECTRICAL:

Impedance:	50 Ω Nominal.
Frequency:	DC - 4 GHz.
VSWR:	1.25:1 Max.
Input Power:	Heat Sink 100°C: 20 Watts. (Derate Power Linearly To 0 Watts @ 125°C).

2. ENVIRONMENTAL:

Non-Operating Temperature: -55°C To +150°C.

Operating Temperature: -55°C To +125°C.

3. MARKING:

Unit Marking: No Marking.

4. QUALITY ASSURANCE:

Sample Inspect Per ANSI/ASQC Z1.4 General Inspection, Level II, AQL = 1.0.

Visual And Mechanical Per 824W154.

DC Resistance: 50 $\Omega \pm 5\%$.

Data Requirements:

No Test Data Required for Customer.

Data Retention – Standard.



5. PACKAGING:

Standard Pack per 755W002.

6. MECHANICAL:

Substrate (Material):	Beryllia, ASTM F356.
Terminals and Ground Plane (Material):	Thick Film, Nickel Barrier, Solder Plated.
Resistive Element (Material):	Thick Film, Tantalum Nitride.
Workmanship:	Per MIL-STD-454, Required 9.

POWER RATING AND DERATING



Dimensions Apply Before Solder. Allow 0.0015 Max for All Pretinned Surfaces.

Unless Otherwise Specified: TOLERANCE: X.XX = ± 0.02 X.XXX = ± 0.010 .