


ORDERING INFORMATION

PART IDENTIFIER:

33-1021-XX.XX

Attenuation Value



SPECIFICATIONS

1. ELECTRICAL:

Nominal Impedance:	50 ohms
Frequency Range:	DC – 2.5 GHz
Attenuation Values Available:	1 through 20 dB in 1 dB increments and 30 dB.
Attenuation Accuracy:	1 through 10 dB \pm 0.5 dB 11 through 20 dB \pm 1.0 dB 30 dB \pm 1.25 dB
Input Power CW:	50 watts @ 100°C heat sink, derated linearly to zero power at 150°C
Peak Power:	500 watts (based on 10us pulse width and 1% duty cycle)
VSWR:	1.40:1 Max

2. ENVIRONMENTAL:

Operating Temperature:	-55°C to +150°C
Non-operating Temperature:	-65°C to +150°C
Temperature Coefficient:	+/-200 PPM / °C max

3. MARKING:

Unit Marking:	Logo and Part Number; legibility, and permanency per MIL-STD-130
---------------	--

4. QUALITY ASSURANCE:

Sample Inspect Per MIL-STD-105, Level II, 1.0% AQL.

Visual and Mechanical Examination for Conformance to Outline Drawing Requirements.

Measure Attenuation and VSWR.

Data Retention – Standard



5. PACKAGING:

Standard Packaging:	Tray
---------------------	------

6. MECHANICAL:

Substrate Material:	Beryllium Oxide
Resistive Film:	Thin Film
Cover Material:	Alumina

Tab Material:	Beryllium Copper
Tab Finish:	Tin/Lead
Flange Material:	Copper
Flange Finish:	Nickel
Metric Dimensions:	Provided for reference only.



Unless Otherwise Specified: TOLERANCE: X.XX = ± 0.02 X.XXX = ± 0.010