


ORDERING INFORMATION

PART IDENTIFIER:

33-1009-XX.XX

Attenuation Value



SPECIFICATIONS

1. ELECTRICAL:

Nominal Impedance:	50 ohms
Frequency Range:	DC - 1.0 GHz
Attenuation Values Available:	1 through 20 dB in 1 dB increments
Attenuation Accuracy:	1 through 10 dB \pm 0.5 dB 11 through 20 dB \pm 1.0 dB
Input Power CW:	75 watts @ 100°C heat sink, derated linearly to zero power at 150°C
Peak Power:	750 watts (based on 10us pulse width and 1% duty cycle)
VSWR:	1.30:1 Max

2. ENVIRONMENTAL:

Operating Temperature:	-55°C to +150°C
Non-operating Temperature:	-65°C to +150°C
Temperature Coefficient:	+/-200 PPM / °C max

3. MARKING:

Unit Marking:	Logo and Part Number; legibility and permanency per MIL-STD-130
---------------	-----------------------------------------------------------------

4. QUALITY ASSURANCE:

Sample Inspect Per MIL-STD-105, Level II, 1.0% AQL.

Visual and Mechanical Examination for Conformance to Outline Drawing Requirements.

Measure Attenuation and VSWR.

Data Retention – Standard

5. PACKAGING:

Standard Packaging:	Tray
---------------------	------

6. MECHANICAL:



Substrate Material:	Beryllium Oxide
Resistive Film:	Thin Film
Cover Material:	Alumina
Tab Material:	Beryllium Copper

ATTENUATOR FLANGE MOUNT 75 WATT

DATASHEET PART SERIES: 33-1009-XX.XX

Sheet 2 of 2
Doc# 33-1009ECO-083524
Revision -

Tab Finish: Tin/Lead
 Flange Material: Copper
 Flange Finish: Nickel
 Metric Dimensions: Provided for reference only.



Unless Otherwise Specified:

TOLERANCE: X.XX = ± 0.02 X.XXX = ± 0.010