



ATTENUATOR TEMPERATURE VARIABLE

DATASHEET PART SERIES:AN3-XNXF

Sheet 1 of 3

ECO-083699

Doc# AN3-XNXF-1011285

Revision E

ORDERING INFORMATION

Part Identifier:

AN3-XNXF

X-Temperature Coefficient of Attenuation 1×10^{-3} dB/dB/°C
 N-Attenuation Shift Negative
 X-dB Value



SPECIFICATIONS

1.0 ELECTRICAL

Nominal Impedance:	50 ohms
Frequency Range:	DC – 4 GHz
Attenuation Values Available:	1-10 dB in 1 dB increments
Attenuation Accuracy:	@ 25°C: ± 0.5 dB @ 1GHz
VSWR:	1.35:1 Max
Input Power	2 Watts Full Rated Power To 100°C, Derated Linearly to 0 Watts at 125°C.
Temperature Coefficient of Attenuation:	-0.003, -0.004, -0.005, -0.006, -0.007, and -0.009 dB/dB/°C
Temperature Coefficient Tolerance:	± 0.001 dB/dB/°C

2.0 ENVIRONMENTAL

Operating Temperature:	-55°C to +150°C
------------------------	-----------------

3.0 MARKING

Unit Marking:	dB Value (XX), Direction of Shift (N) And TCA Shift (X).
---------------	--

4.0 QUALITY ASSURANCE

Sample Inspect Per ANSI/ASQC Z1.4 General Inspection, Level II, AQL=1.0.

Visual and Mechanical Examination for Conformance to Outline Drawing Requirements

Sample Inspection (Destructive Testing).

Select three (3) units from lot and measure DCA every 20°C over the temperature range of -55°C to +125°C; Calculate using linear regression, the slope of the curve.
 Calculate TCA using the following formula:

$$TCA = \frac{\text{Slope}}{\text{Attenuation @ 25°C}}$$

Inspection in accordance with 824W107

Test Data Requirements:

No Data Required for Customer

Data Retention – 24 Months

5.0 PACKAGING

Standard:	Tape and Reel
-----------	---------------



ATTENUATOR TEMPERATURE VARIABLE

DATASHEET PART SERIES:AN3-XNXF

Sheet 2 of 3


ECO-083699

Doc# AN3-XNXF-1011285

Revision E

6.0 MECHANICAL

Substrate Material: Alumina
Terminal Material: Thick Film, Lead Free Plating
Workmanship: PER MIL-PRF-55342
Resistive Element: Thick Film
Metric Dimensions: Provided for reference only



Unless Otherwise Specified: TOLERANCE: X.XXX = ± 0.005




ATTENUATOR TEMPERATURE VARIABLE

DATASHEET PART SERIES:AN3-XNXF

Sheet 3 of 3
Doc# AN3-XNXF-1011285ECO-083699
Revision E

7.0 FOOTPRINT

Part Number	Inches						mm					
	A	B	C	D	S	W	A	B	C	D	S	W
AN3-XNXF	0.043	0.063	0.067	0.035	0.032	0.152	1.09	1.60	1.70	0.89	0.81	3.86



AMERICAS

Sales: Focom.uscsr@smithsinterconnect.comTechnical Support: Focom.techsupport@smithsinterconnect.com

EUROPE

Sales: Focom.emeasr@smithsinterconnect.comTechnical Support: Focom.techsupport@smithsinterconnect.com

ASIA

Sales: Focom.asiacsr@smithsinterconnect.comTechnical Support: Focom.techsupport@smithsinterconnect.com