


## ORDERING INFORMATION

## PART IDENTIFIER:

83-7999-XX.XX

Attenuation Value



## SPECIFICATIONS

## 1. ELECTRICAL:

Nominal Impedance:	50 $\Omega$
Frequency Range:	DC – 3.0 GHz
Attenuation Values Available:	1 through 20 dB in 1 dB increments
Attenuation Accuracy:	1 through 10 dB $\pm 0.5$ dB 11 through 20 dB $\pm 1.0$ dB
Input Power CW:	10 watts @ 100°C heat sink, derated linearly to zero power at 150°C
Peak Power:	100 watts (based on 10 $\mu$ s pulse width and 1% duty cycle)
VSWR:	1.50:1 Max

## 2. ENVIRONMENTAL:

Operating Temperature:	-55°C to +150°C
Non-operating Temperature:	-65°C to +150°C
Temperature Coefficient:	+/-200 PPM / °C max

## 3. MARKING:

Unit Marking:	None
---------------	------

## 4. QUALITY ASSURANCE:

Sample Inspect Per MIL-STD-105, Level II, 1.0% AQL.

Visual and Mechanical Inspection for Conformance to Outline Drawing.

Measure Attenuation and VSWR.

Data Retention – Standard.

## 5. PACKAGING:



Standard Packaging:	Tape and Reel
---------------------	---------------

## ATTENUATOR CHIP 10 WATT

DATASHEET PART SERIES: 83-7999-XX.XX

Sheet 2 of 2  
Doc# 83-7999ECO-083803  
Revision A**6. MECHANICAL:**

Substrate Material: Aluminum Nitride  
 Resistive Film: Thin film  
 Terminal Material: Tin Lead  
 Metric Dimensions: Provided for reference only.



Unless Otherwise Specified: TOLERANCE: X.XX =  $\pm 0.02$  X.XXX =  $\pm 0.010$