


TITLE: SPECIFICATION CONTROL DRAWING

PART IDENTIFIER: TT5XXXXF



DESCRIPTION: CHIP ATTENUATOR, ROHS COMPLIANT

ASSEMBLY DWG: 1902084

1.0 SPECIFICATIONS

1.1 ELECTRICAL

- 1.1.1 IMPEDANCE: 50 OHMS NOMINAL.
- 1.1.2 FREQUENCY RANGE: DC-18GHZ
- 1.1.3 ATTENUATION VALUES AVAILABLE: 0-20DB IN 0.5DB INCREMENTS.
- 1.1.4 ATTENUATION ACCURACY: SEE TABLE.

ATTENUATION ACCURACY				
DB	DC - 4 GHZ	4 - 8 GHZ	8 - 12.4 GHZ	12.4 - 18 GHZ
0	-0,+3	-0,+5	-0,+5	-0,+5
1 -3	±0.3	±0.5	±0.5	±0.5
4 - 6	±0.4	±0.5	±0.5	±0.75
7 - 10	±0.5	±0.5	±0.75	±1.0
11 - 15	±0.75	+0.5,-3.0	+0.5,-3.5	---
16 - 20	±1.0	+0.5,-4.0	+1.0,-6.0	---

- 1.1.5 VSWR: 1.30 MAX.
- 1.1.6 INPUT POWER: 100 MILLIWATTS CW.
 - 1.1.6.1 FULL RATED POWER TO 125°C, DERATED LINEARLY TO 0 WATTS AT 150°C.
 - 1.1.6.2 PEAK POWER, 1 WATT FOR 10US PULSE WIDTH @ 1% DUTY CYCLE.

1.2 MECHANICAL:

- 1.2.1 OUTLINE DWG: SEE SHEET 2.
- 1.2.2 WORKMANSHIP: PER MIL-PRF-55342.

1.3 ENVIRONMENTAL:

- 1.3.1 ALTITUDE:
 - 1.3.1.1 NON-OPERATING: SEA LEVEL TO 50,000 FEET.
 - 1.3.1.2 OPERATING: SEA LEVEL TO 50,000 FEET.
- 1.3.2 TEMPERATURE RANGE:
 - 1.3.2.1 NON-OPERATING: -55 C TO +150 C.
 - 1.3.2.2 OPERATING: -55°C TO +150°C.
- 1.3.3 VIBRATION: PER MIL-STD-202, METHOD 204, COND. D.
- 1.3.4 SHOCK: PER MIL-STD-202, METHOD 213, COND. I.
- 1.3.5 MOISTURE RESISTANCE: PER MIL-STD-202, METHOD 106 EXCEPT SUBCYCLE STEPS 7A AND 7B AND POLARIZATION NOT APPLICABLE.


2.0 UNIT MARKING: MARKED WITH DB VALUE.
LEGIBILITY AND PERMANENCY PER MIL-STD-130.

3.0 QUALITY ASSURANCE:

- 3.1 SAMPLE INSPECT PER ANSI/ASQC Z1.4 GENERAL INSPECTION, LEVEL II, AQL = 1.0.
 - 3.1.1 VISUAL AND MECHANICAL EXAMINATION FOR CONFORMANCE TO OUTLINE DRAWING REQUIREMENTS.
- 3.2 PERFORM INSPECTION IN ACCORDANCE WITH 824W170 AND 824F036 FOR COMMERCIAL GRADE PRODUCT.
- 3.3 TEST DATA REQUIREMENTS:
 - 3.3.1 NO TEST DATA REQUIRED FOR CUSTOMER.
 - 3.3.2 DATA RETENTION – 24 MONTHS

4.0 PACKAGING: STANDARD PACKING PER 755W002.


EMC TECHNOLOGY 8851 SW OLD KANSAS AVE. STUART, FL 34997	CAGE CODE # 24602		DWG #	1011565000
	CHANGE NOTICE	EN 10-E0351	REV LVL	B
			SHEET	1 OF 2



MECHANICAL SPECIFICATIONS:

- SUBSTRATE:
MATERIAL - ALUMINA 96%, MIL-I-10.
- TERMINAL:
MATERIAL - THICK FILM, LEAD FREE, PLATING
RoHS COMPLIANT.
- RESISTIVE ELEMENT:
MATERIAL - THIN FILM, TANTALUM NITRIDE.

POWER RATING AND DERATING



METRIC EQUIVALENTS GIVEN IN [mm]
FOR REFERENCE INFORMATION ONLY



8851 SW OLD KANSAS AVE
STUART, FL 34997
PHONE NO. (772)286-9300
FAX NO. (772)283-5286

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES
TOLERANCES
FRACT ---
ANG ---
XX ---
XXX ±0.005
XXXX ---

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EMC TECHNOLOGY INC AND SHALL NOT BE DUPLICATED OR USED AS BASIS FOR THE MANUFACTURE OR SALE OF PARTS OR DEVICES WITHOUT PERMISSION.

CAGE CODE	SCALE	DRAWN BY	CHECKED BY	APPROVED BY
24602	1:1	JG 3/10/10		
REV	CHANGE NOTICE	DRAWING NO	SHEET	
B	EN 10-E0351	1011565000	2 OF 2	