

ATTENUATOR HIGH RELIABILITY CHIP 2 WATT

DATASHEET PART SERIES: HRTXXXXXXXWB1



Sheet 1 of 2

ECO-084379

Doc# HRTXXXXXXXWB1-1009775

Revision C

ORDERING INFORMATION

Part Identifier: **HRTXX X XX XXWB1**

SPECIFICATIONS

1.0 ELECTRICAL

Nominal Impedance:	50 Ω .
Frequency Range:	DC – 6 GHz.
Attenuation Values Available:	1 – 10 in 1 dB increments.
Attenuation Accuracy @ 25°C:	± 0.5 dB @ 1 GHz.
VSWR:	1.30:1 Max @ 1 GHz.
Input Power CW:	Negative shifting: 2 watts cw. Positive shifting: 0.25 watts cw. Full rated power to 125°C, derated linearly to 0 watts at 150°C.
Temperature Coefficient of Attenuation:	-0.003, -0.004, -0.005, -0.006, -0.007, and -0.009 dB/dB/°C.
Temperature Coefficient Tolerance:	± 0.001 dB/dB/°C.

2.0 ENVIRONMENTAL

Operating Temperature:	-55°C to +150°C.
------------------------	------------------

3.0 MARKING

Unit Marking:	None.
---------------	-------

4.0 QUALITY ASSURANCE

Visual Inspection Performed per TP-8965.

Perform Group A, B and/or C testing as indicated by the part number per TP-8965.

Test Data requirements:

Test data required for customer see TP-8965.

Data retention – 24 months.

Test samples required for customer see TP-8965.

5.0 PACKAGING

Standard Packaging:	Waffle Pack.
---------------------	--------------

ATTENUATOR HIGH RELIABILITY CHIP 2 WATT

DATASHEET PART SERIES: HRTXXXXXXXXWB1

Sheet 2 of 2


ECO-084379

Doc# HRTXXXXXXXXWB1-1009775

Revision C

6.0 MECHANICAL

Substrate Material: Alumina, 96%, MIL-I-10.
 Resistive Film: Thick Film.
 Terminal Material: Thick Film, Bondable Gold.
 Metric Dimensions: Provided for reference only.
 Workmanship: PER MIL-PRF-55342.



Unless Otherwise Specified: TOLERANCE: X.XXX = ± 0.005.