



*Light*CONEX

Optical plug-in and backplane module connectors for VPX systems



LightCONEX

Optical plug-in and backplane module connectors for VPX systems




The *LightCONEX*® series of optical plug-in and backplane module connectors for VPX systems is Smiths Interconnects' answer to the stringent SWaP requirements of today's defense applications in which fiber optics are replacing high bandwidth copper interconnects.

This VPX series of active, blind-mate optical interconnect solutions offer flexibility, light weight, very high bandwidth, and forward compatibility.

The *LightCONEX* active blind mate optical interconnect is a revolutionary solution for VPX systems that includes a fixed, plug-in module connector and a floating backplane connector that have been developed to be compliant with the forthcoming VITA 66.5 standard and in alignment with the SOSA™ technical standard.

The low-profile plug-in module connector is screwed on the board edge through an interposer, saving board space and eliminating fiber cable handling. The backplane connector has a spring-loaded mechanical transfer (MT) ferrule to ensure a secure optical mating connection under extreme shock and vibration conditions.



This Interface Concept 3U VPX card uses a *LightCONEX* LC 12TRX, 120G (full duplex) Style A.

VPX optical interconnect designed to meet the defense industry requirements

Key advantages

- Increases volumetric density of 3U and 6U high-speed switch and payload VPX boards by integrating optical transceiver into plug-in connector.
- Intermateability with VITA 66.5-defined backplane connectors enables multiple sources and drives faster design cycles.
- Reduces optical interconnect SWaP with rugged, MIL-STD qualified, edge-mounted, optical interconnects.
- Enables ultra-high port bandwidth density of up to 720 Gbps full-duplex in a half-width slot.
- Simplifies VPX board assembly and rework by eliminating fiber pigtail on edge-mount transceiver.

Configurations

10.3125G

- 4TRX (40G, full duplex)
- 12TX or 12RX (120G)
- 12TRX (120G, full duplex)


28G

- 4TRX (100G, full duplex),
- 12TX or 12RX (300G), in development


Applications

- VPX single board computing
- C4ISR embedded systems
- AESA radars
- High-throughput Ethernet switches


LightCONEX Styles A, C, and D product line




Insert and plug-in connectors do not include cables. Cables are ordered separately (see page 7 for ordering information).



LightCONEX plug-in and backplane connector. Style A.



LightCONEX plug-in and backplane connector. Style C.



LightCONEX plug-in and backplane connector. Style D.

Optical backplane module connector features


The *LightCONEX*® optical backplane module connector consists of a connector shell and insert. The shell is designed to provide float for the insert in both the X- and Y-directions to enable alignment of the MT ferrule mating interfaces. The design complies with the ANSI/VITA 66.4 mating requirements with the MT ferrule displacement occurring within the backplane connector.

- Tab guiding feature provides coarse alignment
- Spring-loaded MT ferrule (12-channel or 24-channel)

- Compatible with 12-channel or 24-channel OM3 or OM4 fiber ribbon cable

The main components of the backplane module connector are:

1. Connector shells for VITA 67.3 Module Types C, D, and F.
2. Connector inserts available in VITA 66.5 Styles A, C, and D. The main components of the insert are:
 3. Tab primary guiding feature
 4. MT ferrule(s) with alignment pins
 5. Removable fiber back-clamp
6. Optical cable assembly with spring (several cable options are available).



LightCONEX backplane module connector. Style D shown here. (The Style D connector includes a secondary guiding feature).

Style A

The *LightCONEX* backplane connector insert Style A design is intended for active optical applications utilizing the 0.8 in. board pitch. It is designed to fit into the VITA 67.3 Module Type F aperture. The interface is standardized in VITA 66.5.

- 1x MT only.
- Module connector compatible with VITA 66.4 aperture (0.8 in. pitch).



Insert Style A.



Insert Style C.



Insert Style D.

The *LightCONEX* backplane connectors for the VITA 67.3 apertures are available in two versions:

Style C

The *LightCONEX* backplane connector insert Style C design is intended for active optical applications utilizing the 1 in. board pitch. It is designed to fit into VITA 67.3 Module Types C, D, and E apertures. The interface is standardized in VITA 66.5.

- 1x MT only, or hybrid with 1x MT and 10 nanoRF above

Style D

The *LightCONEX* backplane connector insert Style D design is intended for active optical applications utilizing the 1 in. board pitch. It is designed to fit into VITA 67.3 Module Types C, D, and E apertures. The interface is standardized in VITA 66.5.

- Up to 3x MT, in which case the lower MT ferrule mates with the plug-in module active MT, while the upper MT ferrules on the plug-in side are cabled to mid-board transceivers.

Backplane connector components

Connector shells


Different backplane connector shells are available to accommodate VITA 67.3 apertures:



- 450-00070: Backplane connector shell for Module Type F
- 450-00065: Backplane connector shell for Module Type D
- 450-00066: Backplane connector shell for Module Type C
- 450-00104: Backplane connector shell for Module Type E

Inserts

Backplane module inserts are available in the following configurations:



- 415-00025: Backplane connector insert Style A
- 415-00032: Backplane connector insert Style C
- 415-00051: Backplane connector insert Style D


Optical plug-in module connector features

The *LightCONEX*® plug-in module connector contains the optical transceiver with its MT ferrule, an LGA interposer, and a connector shroud.

- Plug-in module connectors are secured with screws directly to the edge of the host board along with their dedicated LGA interposers.
- 5.6 mm transceiver height
- Up to two additional passive optical ports that are connected with detachable cables to mid-board mounted *LightABLE* transceivers.

The main components of the plug-in module connector are:

1. Connector shroud, with:
 2. Optional additional MT ferrule(s) in positions MT-B and MT-C
 3. Slot primary guiding feature
4. Interposer
5. Optical transceiver (its MT ferrule in position MT-A)



LightCONEX plug-in module connector, Style D shown here.

Style A

The *LightCONEX* plug-in module connector Style A is dedicated for the VITA 66.4 aperture and is a unique style with the slot primary alignment feature located above the optical transceiver.



Plug-in module connector Style A.

Plug-in module connector Style C.

Plug-in module connector Style D.

The *LightCONEX* plug-in module connector for the VITA 67.3 apertures are available in two versions. They have connector shrouds for each respective styles with the slot primary guiding feature located below the optical transceiver.

Style C

- Style C has one optical transceiver.

Style D

- Style D has one optical transceiver and two cabled MT.

Plug-in module connector components

Optical transceiver with connector shroud

The plug-in module connectors are equipped with optical transceivers offering multiple transmit and receive and bandwidth configurations:



- *LightCONEX* 10G LC 4TRX module: for Styles A, C, and D
- *LightCONEX* 10G LC 12RX, 12TX, and 12TRX modules: for Styles A, C, and D
- *LightCONEX* 28G LC 4TRX, 12TX, and 12RX modules: for Style C and D

Interposers

- 415-00005: 2.74 mm, 96 positions. Style A
- 415-00011: 3.03 mm, 233 positions. Style A
- 415-00018: 1 mm, 96 positions. Style C and D
- 415-00019: 1.2 mm, 233 positions. Style C and D
- 415-00041: 1.55 mm, 96 positions. Style C and D



233-position interposer.



96-position interposer.

LightCONEX optical performance

The LightCONEX® 10G LC Series and LightCONEX® 28G LC Series optical modules are available in different configurations. These modules offers flexibility, light weight, very high bandwidth, and forward compatibility.

LightCONEX 10G 4TRX, 12RX, 12TX, and 12TRX optical modules


- **Performance:** 10.3125 Gbps/channel from -40 °C to 85 °C
- **Size:** 5.6 mm high (module and interposer)
- **Ruggedness:** MIL-STD 883 shock and vibration qualified
- **Ingress protection:** Moisture and thermal shock resistant
- **Reach:** up to 300 m, OM3 fiber
- **Sensitivity:** -12 dBm or -9 dBm with BER 10⁻¹²
- **Power consumption:** 1.4 W (12-channel, 10.3125G).
2.8 W (24-channel, 10.3125G)



10G 4TRX optical module, Style C shown.

LightCONEX 28G 4TRX optical modules


- **Performance:** 28 Gbps/lane from -40 °C to 85 °C
- **Size:** 5.6 mm high (module and interposer)
- **Ruggedness:** MIL-STD 883 shock and vibration qualified
- **Ingress protection:** Moisture and thermal shock resistant
- **Reach:** up to 100 m, OM3 fiber
- **Sensitivity:** -7.5 dBm with BER 10⁻¹²
- **Power consumption:** 1.4 W (4+4-lane, 28G)



28G 4TRX optical module, Style D shown.

LightCONEX optical modules dimensions

Type	Style	Length ①	Width ②	Height ③ (w/o connector shroud)	Height ④ (with connector shroud)	
10G	4TRX, 12TX, 12RX	A	23.7	13.8	4.6	9.6
		C				9.5
		D				19.4
	12TRX	A	32.3	13.4	4.6	9.6
		C		13.8		9.5
		D		19.4		
28G	4TRX, 12TX, 12RX	C	28.4	14.1	4.0	9.5
		D				19.4



LightCONEX ordering information

Module style	Product description	Plug in module part number	TRX lanes or TX/RX channels	Sensitivity (dBm)	Interposer part number
A	LightCONEX 10G LC 4TRX transceiver	LCX04A4185321AA	4+4	-9	415-00005
		LCX04A4185323AA	4+4	-12	
	LightCONEX 10G LC 12TRX transceiver	LCX12A4185321AA	12+12	-9	415-00011
C	LightCONEX 10G LC 4TRX transceiver	LCX04C418532101	4+4	9	415-00018
		LCX04C418532302	4+4	-12	
	LightCONEX 10G LC 12TRX transceiver	LCX12C4185321AA	12+12	-9	415-00019
	LightCONEX 28G LC 4TRX transceiver	LCX04C428532502	4+4	-7.5	415-00041
	LightCONEX 28G LC 12TX transmitter	LCT12C428532002*	12	n.a.	415-00018
	LightCONEX 28G LC 12RX receiver	LCR12C428530502*	12	-7	
D	LightCONEX 10G LC 4TRX transceiver	LCX04D418532101	4+4	-9	415-00019
		LCX04D418532301	4+4	-12	
	LightCONEX 10G LC 12TRX transceiver	LCX12D4185321AA	12+12	-9	415-00041
	LightCONEX 28G LC 4TRX transceiver	LCX04D428532502	4+4	-7.5	
	LightCONEX 28G LC 12TX transmitter	LCT12D428532002*	12	n.a.	
	LightCONEX 28G LC 12RX receiver	LCR12D428530502	12	-7	

*: In development

Ordering notes

- 10G versions of 12TX and 12RX are also available.
- A version of the Module E shell is available that uses a half-width slot for 1x optical insert (Style D) and a full width slot for 14x SMPM RF inserts.
- A hybrid version of the Style C plug-in and backplane module connectors is available for 10x nanoRF connector inserts and 1x optical (transceiver on plug-in side).
- See datasheets for cables available for Style D plug-in and backplane module connectors.
Plug-in cables connect the plug-in module connector to additional *LightABLE™* transceivers mounted mid-board.

Fiber optic cable ordering information

Backplane fiber cables

Product description	Fiber configuration	Part number
Backplane 15 cm (6 in.) MT-to-MT fiber cable (10N spring and clip)	1x12	500-00258
Backplane 15 cm (6 in.) MT-to-MT fiber cable (20N spring and clip)	2x12	500-00268
Backplane 15 cm (6 in.) MT-to-MPO fiber cable (10N spring and clip)	1x12	500-00267
Backplane 15 cm (6 in.) MT-to-MPO fiber cable (20N spring and clip)	2x12	500-00266

Plug-in fiber cables

Product description	Fiber configuration	Part number
Plug-in 15cm (6 in.) MT-to-MT fiber cable	1x12	500-00256
Plug-in 15cm (6 in.) MT-to-MT fiber cable	2x12	500-00262
Plug-in 15cm (6 in.) MT-to-breakout fiber cable	2x12 and 1x12	500-00269

Worldwide Support

Connectors

Americas

Sales

connectors.uscsr@smithsinterconnect.com

Technical Support

connectors.ustechsupport@smithsinterconnect.com

Europe

Sales

connectors.emeacsr@smithsinterconnect.com

Technical Support

connectors.emeatechsupport@smithsinterconnect.com

Asia

Sales

asiacsr@smithsinterconnect.com

Technical Support

asiatechsupport@smithsinterconnect.com

Fiber Optics & RF Components

Americas

Sales

focom.uscsr@smithsinterconnect.com

Technical Support

focom.techsupport@smithsinterconnect.com

Europe

Sales

focom.emeacsr@smithsinterconnect.com

Technical Support

focom.techsupport@smithsinterconnect.com

Asia

Sales

focom.asiacsr@smithsinterconnect.com

Technical Support

focom.techsupport@smithsinterconnect.com

Semiconductor Test

Americas

Sales

semi.uscsr@smithsinterconnect.com

Technical Support

semi.techsupport@smithsinterconnect.com

Europe

Sales

semi.emeacsr@smithsinterconnect.com

Technical Support

semi.techsupport@smithsinterconnect.com

Asia

Sales

semi.asiacsr@smithsinterconnect.com

Technical Support

semi.techsupport@smithsinterconnect.com

RF/MW Subsystems

Americas, Europe & Asia

Sales

subsystems.csr@smithsinterconnect.com

Technical Support

subsystems.techsupport@smithsinterconnect.com

Connecting Global Markets

smithsinterconnect.com |    

Copyright© 2024 Smiths Interconnect | All rights reserved | Version 1.3

The information contained within this document is subject at all times to applicable Export Control regulations and legal requirements.